

bema

Winter service

robust, reliable

*technically cost
effective and advanced*

versatile in application



bema

Snow plough

1100
Serie

Attaches to:

- Wheel loaders
- Tractors
- Unimog-Truck
- Forklifts
- Special vehicles

CE

*"A clean
product line"*



www.kehrmaschine.de



- **Wheels** with vulcanized elastic rubber, infinitely adjustable with the adjustment wheel
- **Flexible edge protectors** as protection against damage from curbs and walls
- **Spring apron segments** with vulkolan trim (thickness 20 mm, height 150 mm)
- **Lighting system** and flag holder



- **Roller levelling** stable take-up guide - service free -
- **Hydraulic swivelling** by 2 stable hydraulic jack cylinders (mounted below) and integrated overload protection

Basic configuration

- **Snow plough** twist-proof steel construction with spring apron segments and vulkolan trim (snow plough height 1100 mm, vulkolan strip thickness 20 mm, height 150 mm)
- **Swivelling** mechanically - swivels up to 30° -
- **Super-Elastic rollers** Ø 200 x 80 mm (railsafe) with vulcanized elastic, rubber dust-proof, greasable roller bearings, reinforced forks and double-hardened rim bearings
- **Flexible edge protectors** as protection against damage from curbs and walls
- **Series paint finish** orange RAL 2011
- **CE certification** and operating manual

Optional extra equipment

- **Wheel loader attachment** quick change adaptor with roller levelling - service free -
- **Forklift attachment** with roller levelling - service free -
- **Tractor front linkage attachment** including roll level adjustment; Euro-normed quick action attachment or three-point attachment for older front loaders - service free -
- **Tractor mounted front power lifter** with oscillation power compensation, three-point attachment or collection in quick action triangle mode - service free -
- **Unimog-Truck lift attachment** for universal winter service plate with wheel controlled vertical lifting and wheel levelling (in upper position self arresting). The hydraulic cylinder is mounted suspended cardanially and free floating
- **Hydraulic swivelling 30°** by 2 stable hydraulic jack cylinders and hydraulic connector SVK size 3
- **Hydraulic swivelling 30° with integrated overload protection** by 2 stable hydraulic jack cylinders and hydraulic connector SVK size 3
- **Super-Elastic rollers** Ø 250 x 80 mm (railsafe) with vulcanized elastic rubber, dust-proof, greasable roller bearings, reinforced forks and double-hardened rim bearings
- **Lighting system** (necessary if used on public roads)
- **Flag holder**
- **Special paint finish**
- **Special construction** on request

Technical Data

Snow plough 1100	Type 2250	Type 2500	Type 2750	Type 3000
Width (over all)	2275 mm	2520 mm	2765 mm	3010 mm
Clearing width, swivelled 30°	1970 mm	2180 mm	2395 mm	2600 mm
Standard height (over all)	1100 mm			
Machine weight without extras	approx. 411 kg	approx. 437 kg	approx. 465 kg	approx. 490 kg

bema reserve the right to change the technical data at any time.

Your bema partner:

We do not accept liability for printing errors!



Our company is certified
DIN EN ISO 9001:2000



bema GmbH
Maschinenfabrik

www.kehrmaschine.de