

bema

Winter service

robust, reliable

*technically cost
effective and advanced*

versatile in application



Attaches to:

- **Compact tractor**
- **Small municipal vehicles**
- **Skid-steer loaders**
- **Wheel and yardloaders**
- **Forklifts**
- **Special vehicles**

bema

700
Serie

Snow plough

CE

**"A clean
product line"**



www.kehrmaschine.de



- **Wheels** with vulcanized elastic rubber, infinitely adjustable with the adjustment wheel
- **Flexible edge protectors** as protection against damage from curbs and walls
- **Spring apron segments** with vulkolan trim (thickness 20 mm, height 150 mm)
- **Lighting system** and flag holder



- **Roller levelling** stable take-up guide - service free -
- **Hydraulic swivelling** by 2 stable hydraulic jack cylinders (mounted below) and integrated overload protection

Basic configuration

- **Snow plough** twist-proof steel construction with spring apron segments and vulkolan trim (snow plough height 700 mm, vulkolan strip thickness 20 mm, height 150 mm)
- **Swivelling** mechanically - swivels up to 30° -
- **Supporting wheels** Ø 200 x 50 mm with vulcanized elastic rubber, adjustable height with dust caps
- **Flexible edge protectors** as protection against damage from curbs and walls
- **Series paint finish** orange RAL 2011
- **CE certification** and operating manual

Optional extra equipment

- **Attaches to:**
 - **Municipal tractor** three-point mount cat. I/II or I N, with roller levelling - service free -
 - **Municipal tractor** three-point mount cat. 0 with roller levelling - service free -
 - **Municipal vehicles** mounting plates with roller levelling - service free -
- **Forklift attachment** with roller levelling - service free -
- **Quick change adaptor** with roller levelling for wheel- and yardloaders up to 0,4 m³ bucket capacity - service free -
- **Hydraulic swivelling 30 °** by 2 stable hydraulic jack cylinders and hydraulic connector SVK size 3
- **Hydraulic swivelling 30 ° with integrated overload protection** by 2 stable hydraulic jack cylinders and hydraulic connector SVK size 3
- **Heavy duty wheels Ø200 x 50 mm** (industrial quality) with vulcanized elastic rubber, dust-proof, greasable roller bearings, reinforced forks and double-hardened rim bearings
- **Lighting system** (necessary if used on public roads)
- **Flag holder**
- **Special paint finish**
- **Special construction on request**

Technical Data

Snow plough 700	Type 1300	Type 1550	Type 1800	Type 2050
Width (over all)	1290 mm	1535 mm	1780 mm	2025 mm
Clearing width, swivelled 30°	1150 mm	1350 mm	1550 mm	1750 mm
Standard height (over all)	700 mm			
Machine weight without extras	approx. 153 kg	approx. 167 kg	approx. 178 kg	approx. 190 kg

bema reserve the right to change the technical data at any time.

Your bema partner:

We do not accept liability for printing errors!



Our company is certified
DIN EN ISO 9001:2000



bema GmbH
Maschinenfabrik

www.kehrmaschine.de